

PlastiKote Trade Metal Paint & Primer 400 ml

Ord.-no.: 071023, 071024



Technical Information

Use our all-in-one Metal Paint & Primer spray to protect, improve and paint metal surfaces, from cast iron to railings and metal piping. This advanced lacquer combines primer & paint into one easy-to-use spray paint to help make application simpler and smoother than ever. Suitable for interior or exterior metal surfaces, our Metal Paint & Primer spray paint is hard-wearing and quick-drying, with an attractive black finish that helps to protect against rust and chips.

Quality & properties

- Time-saving application
- Excellent coverage and filling property
- Lasting colour and gloss-finish
- Scratch free and shock proof
- Resistant to petrol, chemicals and weather influences
- Excellent adhesion
- Corrosion preventive

Physical & chemical data

- Base: Alkyd resin
- Colourname: Black
- Degree of gloss:
 - ◊ mat, 10 ±2 GU
 - ◊ gloss, >75 GU
- Efficiency: 400 ML – 1,25-1,75 m²
- Dust dry: 30 min
- Dry to touch: 3 - 4 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

