

## PlastiKote Trade Stain Block 400 ml

Ord.-no.: 071019

### Technical Information



PlastiKote Stain Block spray paint is a high-quality, fast-drying acrylic primer to stop stains from spreading to your finished surface. Based on acrylate resin, Stain Block has excellent isolating and insulating properties - ideal for interior use in plasterwork, wood, concrete and more. Stain Block spray paint can be used to treat surfaces (both treated and untreated) like wood, metal, aluminium, glass, stone and various types of plastic. You can use Stain Block to help cut off stains on mineral surfaces like plaster, as well as wood and concrete. Repaintable with all emulsion lacquers, alkyd and water-based acrylic lacquers.

#### Quality & properties

- Excellent isolating properties
- Excellent coverage
- Non-yellowing
- Fast drying
- Excellent adhesion

#### Physical & chemical data

- Base: Acrylic resin
- Colourname: White
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dust dry: 6 min
- Dry to touch: 60 min
- Overcoatable: 60 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: White 110 °C
- Content: 400 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 30, 2024** – This release replaces all eventually earlier issued versions.