

## PlastiKote Trade High Temperature Paint 400 ml

Ord.-no.: 071018

### Technical Information



PlastiKote Trade High Temperature paint is the perfect solution for adding a smart, uniform finish to surfaces that are regularly exposed to very high temperatures. Our high quality lacquer can be used to paint heat-adjacent surfaces, treated and untreated, from fireplaces to radiators. The spray paint application is easy to use, quick-drying, and gives a high-pigmentation quality dark black finish. It's ideal for giving a smooth, professional finish, and can withstand temperatures up to 200°C.

#### Quality & properties

- Excellent adhesion
- Heat resistant
- Resistant to petrol, chemicals and weather influences
- Heat for 30 to 60 minutes (180°C)
- Heat resistant to 800°C

#### Physical & chemical data

- Base: Silicone resin
- Colourname: Black
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dust dry: 5-10 min
- Dry to touch: 10-15 min
- Completely dry: 30-60 min
- Overcoatable: 30-60 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: Black 800 °C
- Content: 400 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the paint in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 30, 2024** – This release replaces all eventually earlier issued versions.