

PlastiKote Twist & Spray Clear Sealer 400 ml

Ord.-no.: 024000, 024001, 024002



Technical Information

Seal in a look that lasts with PlastiKote Twist & Spray Clear Lacquer spray paint. Our Twist & Spray range is our best-ever spray paint with a premium finish, to make spray painting smoother than ever. Twist & Spray Clear Lacquer is fast drying and gives a highly UV absorbent, water-resistant and rust-resistant finish that won't fade or yellow. Our new, ultra-smooth formula provides flawless coverage on every coat and dries quickly to a tough, durable finish. Add shine with this perfect companion for your next painting project. Suitable for use on wood, metal, and more, it adds a high-gloss top coat that's tough, hard-wearing and resistant to scratches. Clear Lacquer spray paint can be used for many types of applications, both interior and exterior, and our Easy-Spray technology makes spray painting easier, faster and cleaner than ever before. The large finger pad reduces the effort needed to spray by 33%. Spray at any angle - perfect for those hard-to-reach places - while the patented spray-through cap shields fingers for a cleaner spray experience. Plus, our Twist and Lock mechanism means there is no separate top to remove or replace after use.

Quality & properties

- Easy-spray technology
- Twist & Lock mechanism
- Water resistant & UV absorbent
- Protects against rust
- Excellent coverage

Physical & chemical data

- Base: Polyester resin
- Colourname: Clear
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ semi gloss, 45 ±5 GU
 - ◊ mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25 - 1,75 m²
- Dust dry: 40-60 min
- Dry to touch: 3-4 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com