

PlastiKote SUPER Primer 400 ml

Ord.-no.: 011145, 011148

Technical Information



PlastiKote SUPER Primer spray paint is the perfect companion for your next painting project. Suitable for use on wood, metal, and more, it adds a preparatory coating that helps paint to adhere far better than when used alone. Our SUPER spray paint is tough, hard-wearing and resistant to scratches. Super Primers and paints are fast drying and give a highly UV absorbent, water-resistant and rust-resistant finish that won't fade or yellow. SUPER Primer spray paint can be used for many types of applications, both interior and exterior. Use after initial preparation before a top coat is applied. Not for use on high impact styrene, leather, Styrofoam and vinyl.

Quality & properties

- Multi-purpose spray paint for use on virtually any surface
- Suitable for indoors and outdoors applications
- Quick-drying
- Optimizes the gloss of the top coat
- Good coverage and filling power

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ White
 - ◊ Grey
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1,5 m²
- Dust dry: 20-40 min
- Dry to touch: 1-2 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces:
 - ◊ wood, metal, aluminium, glass, stone and various types of plastic
 - ◊ a range of interior and exterior decorating applications.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

