

PlastiKote SUPER Colours 400 ml

Ord.-no.: look at ordering information

Technical Information



PlastiKote SUPER Spray Paint is a brilliant choice for your next painting project, with a range of finishes to suit your chosen application. It can be used for many types of applications, both interior and exterior. Super Spray Paint is suitable for use on wood, metal, and more, and comes in a wide range of colours with gloss, satin, and matt finishes. An excellent multi-purpose, multi-surface spray paint, it's tough, hard-wearing and resistant to scratches. SUPER Spray Paint is fast drying and gives a highly UV absorbent, water-resistant and rust-resistant finish. Not for use on high impact styrene, leather, Styrofoam and vinyl.

Quality & properties

- Multi-purpose spray paint for use on virtually any surface
- Suitable for indoors and outdoors applications
- Gloss and matt
- Excellent flow for even surfaces
- Resistant to weathering, light-proof, UV-resistant

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ Black
 - ◊ White
 - ◊ Antique White
 - ◊ Yellow
 - ◊ Orange
 - ◊ Bright Red
 - ◊ Lawn Green
 - ◊ Royal Blue
 - ◊ Light Blue
 - ◊ Aluminium
 - ◊ Gold
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ mat, 10 ±2 GU
- Efficiency: 400 ML – 1,5 m²
- Dust dry:
 - ◊ 40-60 min
 - ◊ 5-10 min
- Dry to touch:
 - ◊ 3-4 min
 - ◊ 10-20 min
- Completely dry:
 - ◊ 24 h
 - ◊ 60 min
- Overcoatable:
 - ◊ 24 h
 - ◊ 60 min
- Surfaces:
 - ◊ wood, metal, aluminium, glass, stone and various types of plastic
 - ◊ a range of interior and exterior decorating applications.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com