

PlastiKote Fast Dry Enamel Colours 400 ml

Ord.-no.: look at ordering information



Technical Information

Add a pop of colour to your DIY projects, crafts, and more, with PlastiKote Fast Dry Enamel Colour spray paint in a brilliant range of colours. Our 400ml spray paint is great for crafts and furniture upcycling. It's resistant to weather, wear, and corrosion and perfect for use on interior and exterior surfaces, including wood, metal, aluminium, glass, stone and various types of plastic. Our superior quality paint is ideal for small upcycling projects, hobbies, or for use in arts and crafts. Our range of Enamel spray paints are easy to use and give great coverage, making it easy to add a polished look to your projects with a non-fading and long-lasting finish. Plus, our Fast Drying technology gives a touch-dry finish in 20-30 minutes.

Quality & properties

- Excellent coverage
- Lasting colour and lasting gloss
- Scratch free and wear-resistant
- Excellent vertical stability so hardly any dripping
- Resistant to chemicals and weather influences
- Excellent adhesion

Physical & chemical data

- Colourname:
 - ◊ Gold
 - ◊ Silver
 - ◊ White
 - ◊ Black
 - ◊ Kernow Cream
 - ◊ Candy Red
 - ◊ Cyan Blue
 - ◊ Heather Pink
 - ◊ Bumblebee Yellow
 - ◊ Pebble Grey
 - ◊ Fir Tree Green
 - ◊ Mexican Lime Green
 - ◊ Tangerine Orange
 - ◊ Clover Green
 - ◊ Lavender violet
 - ◊ Baby Pink
 - ◊ Shortbread beige
 - ◊ Mocha Brown
 - ◊ Sapphire Navy Blue
 - ◊ Silver Grey
- Degree of gloss:
 - ◊ high gloss, >85 GU
 - ◊ gloss, >75 GU
 - ◊ semi gloss, 45 ±5 GU
 - ◊ mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25 - 1,75 m²
- Dust dry: 5 min
- Dry to touch: 10 min
- Completely dry: 60 min
- Overcoatable: 60 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust, sand the surface and apply a layer of Fast Dry Enamel primer.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com