

PlastiKote Radiator 400 ml

Ord.-no.: look at ordering information



Technical Information

PlastiKote Twist and Spray Radiator spray paint has been specially formulated to make painting radiators quick and easy. Our Radiator spray paint range is available in gloss and satin finishes. Looking for a way to keep your radiators looking neat and clean, and give them a new lease of life? Our Radiator spray paint is the perfect solution. There are no brushes to clean and you won't be left with brush marks on your radiator. Most importantly, the formula is non-yellowing and resists heat up to 100°C. Plus, our new easy-spray technology provides added control to make spray painting easier, faster and cleaner. The can's large, comfortable finger pad requires 35% less finger pressure than other spray paint cans, and the twist and lock mechanism means there is no separate top to remove or replace after use. The cap and button design shields the finger from paint for a cleaner spray-painting process.

Quality & properties

- Quick and easy to use
- Non yellowing formula
- Resists heat up to 100°C
- Available in gloss and satin finishes
- Indoor use only

Physical & chemical data

- Base:
 - ◊ Alkyd resin
 - ◊ Acrylic resin
- Colourname:
 - ◊ White
 - ◊ Magnolia
 - ◊ Chrome
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ semi gloss, 45 ±5 GU
- Efficiency: 400 ML – 1,5 m²
- Dust dry:
 - ◊ 40 - 60 min
 - ◊ 5 - 10 min
- Dry to touch:
 - ◊ 3 - 4 h
 - ◊ 10 - 20 min
- Completely dry:
 - ◊ 24 h
 - ◊ 1 h
- Overcoatable:
 - ◊ 24 h
 - ◊ 1 h
- Surfaces: radiator
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 3500/20 bar
 - ◊ 4000/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com