

PlastiKote Glitter 400 ml

Ord.-no.: 440172, 440173

Technical Information



Looking to add a little sparkle to your space? For a beautiful glitter effect, use PlastiKote Glitter spray paint as a top coat to create a stunning finish to any of your classic household items. Want to add some shine to an old photo frame, or make some magic with some old dolls house furniture? As long as it's not going to go near any little mouths, our glittery top coat is the perfect choice for this little home DIY projects. Perfect for adding a touch of glamour and sophistication to boxes, frames, and other small objects around the home, PlastiKote Glitter isn't just for the kids though. You can make any space in your home look more personalised with a touch of sparkle. We would recommend reading the instructions on the can very carefully before you begin any projects, and spraying it on a hidden area first to make sure you're going to love it.

Quality & properties

- Gives a stunning glitter finish
- Ideal for use on small decorative projects
- Good flow, smooth surface
- Excellent adhesion
- Unique finish

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - ◊ Gold Glitter
 - ◊ Silver Glitter
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 3 m²
- Dust dry: 5 min
- Dry to touch: 10 min
- Completely dry: 20 min
- Overcoatable: Anytime min
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

