

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

Article number: 414003

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category Paint remover

### Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Spray varnish

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

European Aerosols B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel : +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

Further information obtainable from: Department Product Safety

### 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



STOT SE 3 H336 May cause drowsiness or dizziness.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word** *Danger***· Hazard-determining components of labelling:***1-methoxy-2-propanol**propan-2-ol***· Hazard statements***H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.**H336 May cause drowsiness or dizziness.***· Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P260 Do not breathe spray.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents / container in accordance with regional regulations.***· Additional information:***Buildup of explosive mixtures possible without sufficient ventilation.***· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

|   |  |           |
|---|--|-----------|
| CAS: 115-10-6<br>EINECS: 204-065-8<br>Index number: 603-019-00-8<br>Reg.nr.: 01-2119472128-37 | <i>dimethyl ether</i><br>⚠ Flam. Gas 1A, H220<br>⚠ Press. Gas (Comp.), H280  | 50-<75%   |
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Index number: 603-064-00-3<br>Reg.nr.: 01-2119457435-35 | <i>1-methoxy-2-propanol</i><br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336   | 20-<25%   |
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Index number: 603-002-00-5<br>Reg.nr.: 01-2119457610-43  | <i>ethanol</i><br>⚠ Flam. Liq. 2, H225<br>⚠ Eye Irrit. 2, H319<br>Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 % | 12.5-<20% |
| CAS: 9004-70-0  | <i>cellulose nitrate</i><br>⚠ Expl. 1.1, H201  | 2.5-<5%   |
| CAS: 111-76-2<br>EINECS: 203-905-0<br>Index number: 603-014-00-0<br>Reg.nr.: 01-2119475108-36 | <i>2-butoxyethanol</i><br>⚠ Acute Tox. 3, H331<br>⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319              | 2.5-<5%   |

(Contd. on page 3)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**



CAS: 67-63-0

EINECS: 200-661-7

Index number: 603-117-00-0

Reg.nr.: 01-2119457558-25

propan-2-ol

 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336

(Contd. of page 2)

2.5-&lt;5%

**Additional information:**

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

**5.3 Advice for firefighters -**

- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

**6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.****6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

(Contd. on page 4)

GB

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · **Ingredients with limit values that require monitoring at the workplace:**

###### **115-10-6 dimethyl ether**

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

###### **107-98-2 1-methoxy-2-propanol**

WEL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
Sk

###### **64-17-5 ethanol**

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

###### **111-76-2 2-butoxyethanol**

WEL Short-term value: 246 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 123 mg/m<sup>3</sup>, 25 ppm  
Sk, BMGV

###### **67-63-0 propan-2-ol**

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

#### · **DNELs**

##### **107-98-2 1-methoxy-2-propanol**

|            |      |  |
|------------|------|--|
| Oral       | DNEL | 3.3 mg/kg /per day (Consumer, longterm systemic)     |
| Dermal     | DNEL | 50.6 mg/kg /per day (Worker, longterm systemic)      |
|            | DNEL | 18.1 mg/kg /per day (Consumer, longterm systemic)    |
| Inhalative | DNEL | 553.5 mg/m <sup>3</sup> (Worker, acute local)        |
|            | DNEL | 369 mg/m <sup>3</sup> (Worker, longterm systemic)    |
|            | DNEL | 43.9 mg/m <sup>3</sup> (Consumer, longterm systemic) |

##### **64-17-5 ethanol**

|            |      |   |
|------------|------|---|
| Oral       | DNEL | 87 mg/kg /per day (Consumer, longterm systemic)     |
| Dermal     | DNEL | 343 mg/kg /per day (Worker, longterm systemic)      |
|            | DNEL | 206 mg/kg /per day (Consumer, longterm systemic)    |
| Inhalative | DNEL | 950 mg/m <sup>3</sup> (Worker, longterm systemic)   |
|            | DNEL | 1900 mg/m <sup>3</sup> (Worker, acute local)        |
|            | DNEL | 114 mg/m <sup>3</sup> (Consumer, longterm systemic) |
|            | DNEL | 950 mg/m <sup>3</sup> (Consumer, acute local)       |

##### **111-76-2 2-butoxyethanol**

|      |      |   |
|------|------|---|
| Oral | DNEL | 3.2 mg/kg (Consumer, longterm systemic) |
|      | DNEL | 13.4 mg/kg (Consumer, acute systemic)   |

(Contd. on page 5)

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 4)

|                   |             |  |
|-------------------|-------------|--|
| <i>Dermal</i>     | <i>DNEL</i> | 75 mg/kg /per day (Worker, longterm systemic)  |
|                   | <i>DNEL</i> | 89 mg/kg /per day (Worker, acute systemic)     |
|                   | <i>DNEL</i> | 38 mg/kg (Consumer, longterm systemic)         |
|                   | <i>DNEL</i> | 44.5 mg/kg /per day (Consumer, acute systemic) |
| <i>Inhalative</i> | <i>DNEL</i> | 98 mg/m3 /20 ppm (Worker, longterm systemic)   |
|                   | <i>DNEL</i> | 663 mg/m3 /135 ppm (Worker, acute systemic)    |
|                   | <i>DNEL</i> | 246 mg/m3 /50 ppm (Worker, acute local)        |
|                   | <i>DNEL</i> | 49 mg/m3 (Consumer, longterm systemic)         |
|                   | <i>DNEL</i> | 426 mg/m3 (Consumer; acute systemic)           |
|                   | <i>DNEL</i> | 123 mg/m3 (Consumer, acute local)              |

**67-63-0 propan-2-ol**

|                   |             |  |
|-------------------|-------------|--|
| <i>Oral</i>       | <i>DNEL</i> | 26 mg/kg /per day (Consumer, longterm systemic)  |
| <i>Dermal</i>     | <i>DNEL</i> | 888 mg/kg /per day (Worker, longterm systemic)   |
|                   | <i>DNEL</i> | 319 mg/kg /per day (Consumer, longterm systemic) |
| <i>Inhalative</i> | <i>DNEL</i> | 500 mg/m3 (Worker, longterm systemic)            |
|                   | <i>DNEL</i> | 89 mg/m3 (Consumer, longterm systemic)           |

**· PNECs****107-98-2 1-methoxy-2-propanol**

|             |                                   |
|-------------|-----------------------------------|
| <i>PNEC</i> | 10 mg/l (Freshwater)              |
| <i>PNEC</i> | 1 mg/l (Seawater)                 |
| <i>PNEC</i> | 100 mg/l (Sporadic release)       |
| <i>PNEC</i> | 100 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 52.3 mg/kg (Freshwater sediment)  |
| <i>PNEC</i> | 5.2 mg/kg (Seawater sediment)     |
| <i>PNEC</i> | 4.59 mg/kg (Soil)                 |

**64-17-5 ethanol**

|             |                                   |
|-------------|-----------------------------------|
| <i>PNEC</i> | 0.96 mg/l (Freshwater)            |
| <i>PNEC</i> | 0.79 mg/l (Seawater)              |
| <i>PNEC</i> | 2.75 mg/l (Sporadic release)      |
| <i>PNEC</i> | 580 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 3.6 mg/kg (Freshwater sediment)   |
| <i>PNEC</i> | 2.9 mg/kg (Seawater sediment)     |
| <i>PNEC</i> | 0.63 mg/kg (Soil)                 |

**111-76-2 2-butoxyethanol**

|             |                                   |
|-------------|-----------------------------------|
| <i>PNEC</i> | 8.8 mg/l (Freshwater)             |
| <i>PNEC</i> | 0.88 mg/l (Seawater)              |
| <i>PNEC</i> | 9.1 mg/l (Sporadic release)       |
| <i>PNEC</i> | 463 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 34.6 mg/kg (Freshwater sediment)  |
| <i>PNEC</i> | 3.45 mg/kg (Seawater sediment)    |
| <i>PNEC</i> | 2.8 mg/kg (Soil)                  |

**67-63-0 propan-2-ol**

|             |                               |
|-------------|-------------------------------|
| <i>PNEC</i> | 140.9 mg/l (Freshwater)       |
| <i>PNEC</i> | 140.9 mg/l (Seawater)         |
| <i>PNEC</i> | 140.9 mg/l (Sporadic release) |

(Contd. on page 6)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 5)

|      |                                    |
|------|------------------------------------|
| PNEC | 2251 mg/l (Sewage treatment plant) |
| PNEC | 552 mg/kg (Freshwater sediment)    |
| PNEC | 552 mg/kg (Seawater sediment)      |

· **Ingredients with biological limit values:**

**111-76-2 2-butoxyethanol**

|      |                              |
|------|------------------------------|
| BMGV | 240 mmol/mol creatinine      |
|      | Medium: urine                |
|      | Sampling time: post shift    |
|      | Parameter: butoxyacetic acid |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection** Not required.

· **Material of gloves** Not required.

· **Penetration time of glove material** Not required.

· **Eye/face protection** Not required.

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Colourless

· **Odour:**

Nearly odourless

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.9 Vol % (107-98-2 1-methoxy-2-propanol)

· **Upper:**

26.2 Vol % (115-10-6 dimethyl ether)

· **Flash point:**

Not applicable, as aerosol.

· **Auto-ignition temperature:**

240 °C (464 °F) (115-10-6 dimethyl ether)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

4000 hPa (3000.2 mm Hg)

(Contd. on page 7)



**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 6)

|  |   |
|--|---|
| · <b>Density and/or relative density</b>   |   |
| · <b>Density at 20 °C (68 °F):</b>   | 0.8 g/cm <sup>3</sup> (6.7 lbs/gal)   |
| · <b>Relative density</b>  | Not determined.   |
| · <b>Vapour density</b>  | Not determined.   |
| · <b>9.2 Other information</b>   |   |
| · <b>Appearance:</b>   |   |
| · <b>Form:</b>   | Aerosol   |
| · <b>Important information on protection of health and environment, and on safety.</b> |   |
| · <b>Explosive properties:</b>   | Not determined.   |
| · <b>Solvent content:</b>  |   |
| · <b>Organic solvents:</b>   | 91.7 %  |
| · <b>Water:</b>  | 0.6 %   |
| · <b>VOC (EC)</b>  | ---   |
|  | 715.4 g/l   |
| · <b>VOC-EU%</b>   | 91.67 %   |
| · <b>Solids content:</b>   | 5.0 %   |
| · <b>Change in condition</b>   |   |
| · <b>Evaporation rate</b>  | Not applicable.   |
| · <b>Information with regard to physical hazard classes</b>                            |   |
| · <b>Explosives</b>  | Void  |
| · <b>Flammable gases</b>   | Void  |
| · <b>Aerosols</b>  | Extremely flammable aerosol. Pressurised container:<br>May burst if heated. |
| · <b>Oxidising gases</b>   | Void  |
| · <b>Gases under pressure</b>  | Void  |
| · <b>Flammable liquids</b>   | Void  |
| · <b>Flammable solids</b>  | Void  |
| · <b>Self-reactive substances and mixtures</b>   | Void  |
| · <b>Pyrophoric liquids</b>  | Void  |
| · <b>Pyrophoric solids</b>   | Void  |
| · <b>Self-heating substances and mixtures</b>  | Void  |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b>     | Void  |
| · <b>Oxidising liquids</b>   | Void  |
| · <b>Oxidising solids</b>  | Void  |
| · <b>Organic peroxides</b>   | Void  |
| · <b>Corrosive to metals</b>   | Void  |
| · <b>Desensitised explosives</b>   | Void  |

\*

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 7)

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 64-17-5 ethanol

|            |           |                   |
|------------|-----------|-------------------|
| Oral       | LD50      | 10470 mg/kg (rat) |
| Dermal     | LD50      | >2000 mg/kg (rat) |
| Inhalative | LC50 / 4h | 120 mg/l (rat)    |

##### 111-76-2 2-butoxyethanol

|            |             |   |
|------------|-------------|---|
| Oral       | LD50        | 1200 mg/kg (guinea pig)                               |
| Inhalative | LC50 / 4 h  | 3 mg/m <sup>3</sup> (rat)                             |
|            | LC50 / 96 h | >100 mg/l (oncorhynchus mykiss) (Oncorhynchus mykiss) |

##### 67-63-0 propan-2-ol

|            |      |                      |
|------------|------|----------------------|
| Oral       | LD50 | 5840 mg/kg (rat)     |
| Dermal     | LD50 | 13900 mg/kg (rabbit) |
| Inhalative | LC50 | >25 mg/l (rat)       |
|            |      | LC 50: 6h            |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 115-10-6 dimethyl ether

|             |                            |
|-------------|----------------------------|
| EC50 / 96 h | 155 mg/l (algae)           |
| LC50 / 48 h | >4000 mg/l (daphnia magna) |
| LC50 / 96 h | >4000 mg/l (fish)          |

##### 64-17-5 ethanol

|             |                                  |
|-------------|----------------------------------|
| LC50/96h    | 13000 mg/l (oncorhynchus mykiss) |
| EC50 / 48 h | 12900 mg/l (algae)               |
| LC50 / 48 h | 12340 mg/l (daphnia magna)       |

##### 111-76-2 2-butoxyethanol

|             |   |
|-------------|---|
| LC50 / 48 h | 1550 mg/l (daphnia magna)                   |
| LC50 / 72 h | 1840 mg/l (Pseudokirchneriella subcapitata) |
| LC50 / 96 h | 1474 mg/l (Regenbogenforelle)               |

##### 67-63-0 propan-2-ol

|             |                                      |
|-------------|--------------------------------------|
| LC50/96h    | 9640 mg/l (pimephales promelas; 96h) |
| LC50 / 24 h | 9714 mg/l (daphnia magna)            |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 9)



**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**



(Contd. of page 8)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |                     |
|---|---------------------|
| · <b>14.1 UN number or ID number</b>  | UN1950              |
| · <b>ADR, IMDG, IATA</b>  |                     |
| · <b>14.2 UN proper shipping name</b>   | 1950 AEROSOLS       |
| · <b>ADR</b>  | AEROSOLS            |
| · <b>IMDG</b>   | AEROSOLS            |
| · <b>IATA</b>   | AEROSOLS, flammable |
| · <b>14.3 Transport hazard class(es)</b>  |                     |
| · <b>ADR</b>  |                     |
|  |                     |
| · <b>Class</b>  | 2 5F Gases.         |
| · <b>Label</b>  | 2.1                 |
| · <b>IMDG, IATA</b>   |                     |
|  |                     |
| · <b>Class</b>  | 2.1 Gases.          |
| · <b>Label</b>  | 2.1                 |
| · <b>14.4 Packing group</b>   | not regulated       |
| · <b>ADR, IMDG, IATA</b>  |                     |
| · <b>14.5 Environmental hazards:</b>  | Not applicable.     |
| · <b>14.6 Special precautions for user</b>  | Warning: Gases.     |
| · <b>Hazard identification number (Kemler code):</b>                                | -                   |

(Contd. on page 10)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 9)

|   |   |
|---|---|
| · <b>EMS Number:</b>  | <i>F-D,S-U</i>  |
| · <b>Stowage Code</b>   | <i>SW1 Protected from sources of heat.<br/>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</i>  |
| · <b>Segregation Code</b>   | <i>SG69 For AEROSOLS with a maximum capacity of 1 litre:<br/>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.<br/>For AEROSOLS with a capacity above 1 litre:<br/>Segregation as for the appropriate subdivision of class 2.<br/>For WASTE AEROSOLS:<br/>Segregation as for the appropriate subdivision of class 2.</i> |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b> | <i>Not applicable.</i>  |
| · <b>Transport/Additional information:</b>                            |   |
| · <b>ADR</b>  |   |
| · <b>Limited quantities (LQ)</b>                                      | <i>1L</i>   |
| · <b>Excepted quantities (EQ)</b>                                     | <i>Code: E0<br/>Not permitted as Excepted Quantity</i>  |
| · <b>Transport category</b>   | <i>2</i>  |
| · <b>Tunnel restriction code</b>                                      | <i>D</i>  |
| · <b>IMDG</b>   |   |
| · <b>Limited quantities (LQ)</b>                                      | <i>1L</i>   |
| · <b>Excepted quantities (EQ)</b>                                     | <i>Code: E0<br/>Not permitted as Excepted Quantity<br/>Code: E0<br/>Not permitted as Excepted Quantity</i>  |
| · <b>UN "Model Regulation":</b>                                       | <i>UN 1950 AEROSOLS, 2.1</i>  |

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 11)

GB

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER MATT 6UC 400 ML**

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H201 Explosive; mass explosion hazard.  
 H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H280 Contains gas under pressure; may explode if heated.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H336 May cause drowsiness or dizziness.

· **Classification according to Regulation (EC) No 1272/2008**

*Data is based on internal technical data and technical data from suppliers.*

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Expl. 1.1: Explosives – Division 1.1  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Acute Tox. 3: Acute toxicity – Category 3  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

GB