

## PlastiKote Metal Hammer 400 ml

Ord.-no.: 002215

### Technical Information



PlastiKote Metal Paint Hammer Spray Paint offers a decorative, hammered effect finish, which can be used on most surfaces to achieve a metal-like effect. Metal Hammer spray paint is fast drying and protects against corrosion. It's quick and easy to use and is rust-resistant. Giving a unique and richly textured finish, this hammered metal spray paint is perfect for any project where you want an authentic metal effect with the ease of spray paint. Our unique hammer paint is suitable for use on masonry, metal, plaster, and wood. Giving a uniform and protective finish to any project, PlastiKote Metal Hammer paint is perfect for use where you need a smooth and attractive final surface.

#### Quality & properties

- Provides rust protection and UV resistance
- No primer or sealer required
- Multi-purpose
- Protects against all weather influences
- Fast-drying

#### Physical & chemical data

- Base: Nitrocombi resin
- Colourname: Black
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 0.8 m<sup>2</sup>
- Dust dry: 5-10 min
- Dry to touch: 10-20 min
- Completely dry: 1 h
- Overcoatable: 1 h
- Surfaces: metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Temperature Resistance: Black 110 °C
- Content: 400 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.