

PlastiKote Trade 4 in 1 Rust Paint 400 ml

Ord.-no.: 071022



Technical Information

PlastiKote Trade 4-in-1 Rust Stop Spray Paint provides active corrosion protection using an effective 4-in-1 lacquer system: 1. Primer 2. Corrosion resistance 3. Colour 4. Protection. Our rust protection spray paint formula contains rust-stopping technology by creating a chemical connection between the paint and the surface. The existing oxidation stops, and the paint then creates a durable barrier to protect the surface from further rusting. Rust Stop spray paint has a quick-drying formula that provides high coverage and excellent adhesion on almost all surfaces, even on existing rust. Expect excellent adhesion on almost all surfaces, such as iron, blank and zinc-plated steel plates, copper, brass, aluminium, wood, stone or glass.

Quality & properties

- Durable corrosion protection
- Fast-drying
- Very good flow
- High coverage and filling power
- High elasticity
- Shock-proof and impact resistant after drying
- Excellent adhesion
- UV-resistant, non-yellowing
- Weather-resistant, waterproof

Physical & chemical data

- Base: Acrylic resin
- Colourname: White
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25-1,75 m²
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: White 80 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.