

PlastiKote Trade Quick Dry Primer Undercoat 400 ml

Ord.-no.: 071000, 071001, 071002

Technical Information



Our Quick Dry Primer Undercoat is a fast-drying acrylic primer - a simple spray is all it takes to provide a base layer for all types of paint coatings. Use it on a variety of surfaces including wood, metal, aluminium, plastics, glass and stone. High quality, fast drying, and durable, our Primer Undercoat is a suitable primer as pre-treatment for re-spraying with all lacquer systems (alkyd resin, nitro cellulose, 1-K acrylic and 2-K acrylic lacquers).

Quality & properties

- Fast-drying
- Corrosion preventive
- Excellent coverage and filling properties
- Excellent vertical stability so hardly any dripping
- Easy to sand, both wet and dry (from grain 400)
- Re-sprayable with all lacquer systems

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - ◊ White
 - ◊ Grey
 - ◊ Red oxide
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1,25-1,75 m²
- Dust dry: 15 min
- Dry to touch: 30 min
- Completely dry: 2-4 h
- Overcoatable: 2-4 h
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

