

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML**

Article number: 414001

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category Paint remover

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Spray varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

European Aerosols B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel : +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

Further information obtainable from: Department Product Safety

1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07

· Signal word *Danger***· Hazard-determining components of labelling:***1-methoxy-2-propanol**propan-2-ol***· Hazard statements***H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.**H336 May cause drowsiness or dizziness.***· Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P260 Do not breathe spray.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents / container in accordance with regional regulations.***· Additional information:***Buildup of explosive mixtures possible without sufficient ventilation.***· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

| | | |
|---|--|-----------|
| CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37 | <i>dimethyl ether</i> ⚠ Flam. Gas 1A, H220 ⚠ Press. Gas (Comp.), H280 | 50-<75% |
| CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35 | <i>1-methoxy-2-propanol</i> ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 | 20-<25% |
| CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43 | <i>ethanol</i> ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 % | 12.5-<20% |
| CAS: 9004-70-0 | <i>cellulose nitrate</i> ⚠ Expl. 1.1, H201 | 2.5-<5% |
| CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36 | <i>2-butoxyethanol</i> ⚠ Acute Tox. 3, H331 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | 2.5-<5% |

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML


CAS: 67-63-0

EINECS: 200-661-7

Index number: 603-117-00-0

Reg.nr.: 01-2119457558-25

propan-2-ol

 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336

(Contd. of page 2)

2.5-<5%

Additional information:

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters -

- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

(Contd. on page 4)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

· **DNELs**

107-98-2 1-methoxy-2-propanol

| | | |
|------------|------|--|
| Oral | DNEL | 3.3 mg/kg /per day (Consumer, longterm systemic) |
| Dermal | DNEL | 50.6 mg/kg /per day (Worker, longterm systemic) |
| | DNEL | 18.1 mg/kg /per day (Consumer, longterm systemic) |
| Inhalative | DNEL | 553.5 mg/m ³ (Worker, acute local) |
| | DNEL | 369 mg/m ³ (Worker, longterm systemic) |
| | DNEL | 43.9 mg/m ³ (Consumer, longterm systemic) |

64-17-5 ethanol

| | | |
|------------|------|---|
| Oral | DNEL | 87 mg/kg /per day (Consumer, longterm systemic) |
| Dermal | DNEL | 343 mg/kg /per day (Worker, longterm systemic) |
| | DNEL | 206 mg/kg /per day (Consumer, longterm systemic) |
| Inhalative | DNEL | 950 mg/m ³ (Worker, longterm systemic) |
| | DNEL | 1900 mg/m ³ (Worker, acute local) |
| | DNEL | 114 mg/m ³ (Consumer, longterm systemic) |
| | DNEL | 950 mg/m ³ (Consumer, acute local) |

111-76-2 2-butoxyethanol

| | | |
|------|------|---|
| Oral | DNEL | 3.2 mg/kg (Consumer, longterm systemic) |
| | DNEL | 13.4 mg/kg (Consumer, acute systemic) |

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 4)

| | | |
|-------------------|-------------|--|
| <i>Dermal</i> | <i>DNEL</i> | 75 mg/kg /per day (Worker, longterm systemic) |
| | <i>DNEL</i> | 89 mg/kg /per day (Worker, acute systemic) |
| | <i>DNEL</i> | 38 mg/kg (Consumer, longterm systemic) |
| | <i>DNEL</i> | 44.5 mg/kg /per day (Consumer, acute systemic) |
| <i>Inhalative</i> | <i>DNEL</i> | 98 mg/m3 /20 ppm (Worker, longterm systemic) |
| | <i>DNEL</i> | 663 mg/m3 /135 ppm (Worker, acute systemic) |
| | <i>DNEL</i> | 246 mg/m3 /50 ppm (Worker, acute local) |
| | <i>DNEL</i> | 49 mg/m3 (Consumer, longterm systemic) |
| | <i>DNEL</i> | 426 mg/m3 (Consumer; acute systemic) |
| | <i>DNEL</i> | 123 mg/m3 (Consumer, acute local) |

67-63-0 propan-2-ol

| | | |
|-------------------|-------------|--|
| <i>Oral</i> | <i>DNEL</i> | 26 mg/kg /per day (Consumer, longterm systemic) |
| <i>Dermal</i> | <i>DNEL</i> | 888 mg/kg /per day (Worker, longterm systemic) |
| | <i>DNEL</i> | 319 mg/kg /per day (Consumer, longterm systemic) |
| <i>Inhalative</i> | <i>DNEL</i> | 500 mg/m3 (Worker, longterm systemic) |
| | <i>DNEL</i> | 89 mg/m3 (Consumer, longterm systemic) |

· PNECs**107-98-2 1-methoxy-2-propanol**

| | |
|-------------|-----------------------------------|
| <i>PNEC</i> | 10 mg/l (Freshwater) |
| <i>PNEC</i> | 1 mg/l (Seawater) |
| <i>PNEC</i> | 100 mg/l (Sporadic release) |
| <i>PNEC</i> | 100 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 52.3 mg/kg (Freshwater sediment) |
| <i>PNEC</i> | 5.2 mg/kg (Seawater sediment) |
| <i>PNEC</i> | 4.59 mg/kg (Soil) |

64-17-5 ethanol

| | |
|-------------|-----------------------------------|
| <i>PNEC</i> | 0.96 mg/l (Freshwater) |
| <i>PNEC</i> | 0.79 mg/l (Seawater) |
| <i>PNEC</i> | 2.75 mg/l (Sporadic release) |
| <i>PNEC</i> | 580 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 3.6 mg/kg (Freshwater sediment) |
| <i>PNEC</i> | 2.9 mg/kg (Seawater sediment) |
| <i>PNEC</i> | 0.63 mg/kg (Soil) |

111-76-2 2-butoxyethanol

| | |
|-------------|-----------------------------------|
| <i>PNEC</i> | 8.8 mg/l (Freshwater) |
| <i>PNEC</i> | 0.88 mg/l (Seawater) |
| <i>PNEC</i> | 9.1 mg/l (Sporadic release) |
| <i>PNEC</i> | 463 mg/l (Sewage treatment plant) |
| <i>PNEC</i> | 34.6 mg/kg (Freshwater sediment) |
| <i>PNEC</i> | 3.45 mg/kg (Seawater sediment) |
| <i>PNEC</i> | 2.8 mg/kg (Soil) |

67-63-0 propan-2-ol

| | |
|-------------|-------------------------------|
| <i>PNEC</i> | 140.9 mg/l (Freshwater) |
| <i>PNEC</i> | 140.9 mg/l (Seawater) |
| <i>PNEC</i> | 140.9 mg/l (Sporadic release) |

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML**

(Contd. of page 5)

| | |
|------|------------------------------------|
| PNEC | 2251 mg/l (Sewage treatment plant) |
| PNEC | 552 mg/kg (Freshwater sediment) |
| PNEC | 552 mg/kg (Seawater sediment) |

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

| | |
|------|------------------------------|
| BMGV | 240 mmol/mol creatinine |
| | Medium: urine |
| | Sampling time: post shift |
| | Parameter: butoxyacetic acid |

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection** Not required.

· **Material of gloves** Not required.

· **Penetration time of glove material** Not required.

· **Eye/face protection** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Physical state**

Aerosol

· **Colour:**

Colourless

· **Odour:**

Nearly odourless

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.9 Vol % (107-98-2 1-methoxy-2-propanol)

· **Upper:**

26.2 Vol % (115-10-6 dimethyl ether)

· **Flash point:**

Not applicable, as aerosol.

· **Auto-ignition temperature:**

240 °C (464 °F) (115-10-6 dimethyl ether)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

4000 hPa (3000.2 mm Hg)

(Contd. on page 7)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 6)

| | |
|--|---|
| · Density and/or relative density | |
| · Density at 20 °C (68 °F): | 0.8 g/cm ³ (6.7 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · 9.2 Other information | |
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Explosive properties: | Not determined. |
| · Solvent content: | |
| · Organic solvents: | 91.7 % |
| · Water: | 0.6 % |
| · VOC (EC) | --- |
| | 715.4 g/l |
| · VOC-EU% | 91.67 % |
| · Solids content: | 5.0 % |
| · Change in condition | |
| · Evaporation rate | Not applicable. |
| · Information with regard to physical hazard classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

*

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML**

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

64-17-5 ethanol

| | | |
|------------|-----------|-------------------|
| Oral | LD50 | 10470 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| Inhalative | LC50 / 4h | 120 mg/l (rat) |

111-76-2 2-butoxyethanol

| | | |
|------------|-------------|---|
| Oral | LD50 | 1200 mg/kg (guinea pig) |
| Inhalative | LC50 / 4 h | 3 mg/m ³ (rat) |
| | LC50 / 96 h | >100 mg/l (oncorhynchus mykiss) (Oncorhynchus mykiss) |

67-63-0 propan-2-ol

| | | |
|------------|------|----------------------|
| Oral | LD50 | 5840 mg/kg (rat) |
| Dermal | LD50 | 13900 mg/kg (rabbit) |
| Inhalative | LC50 | >25 mg/l (rat) |
| | | LC 50: 6h |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

115-10-6 dimethyl ether

| | |
|-------------|----------------------------|
| EC50 / 96 h | 155 mg/l (algae) |
| LC50 / 48 h | >4000 mg/l (daphnia magna) |
| LC50 / 96 h | >4000 mg/l (fish) |

64-17-5 ethanol

| | |
|-------------|----------------------------------|
| LC50/96h | 13000 mg/l (oncorhynchus mykiss) |
| EC50 / 48 h | 12900 mg/l (algae) |
| LC50 / 48 h | 12340 mg/l (daphnia magna) |

111-76-2 2-butoxyethanol

| | |
|-------------|---|
| LC50 / 48 h | 1550 mg/l (daphnia magna) |
| LC50 / 72 h | 1840 mg/l (Pseudokirchneriella subcapitata) |
| LC50 / 96 h | 1474 mg/l (Regenbogenforelle) |

67-63-0 propan-2-ol

| | |
|-------------|--------------------------------------|
| LC50/96h | 9640 mg/l (pimephales promelas; 96h) |
| LC50 / 24 h | 9714 mg/l (daphnia magna) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 8)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.



*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

*

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | <p style="text-align: center;">UN1950</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | <p style="text-align: center;">1950 AEROSOLS AEROSOLS AEROSOLS, flammable</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: center;">2 5F Gases. 2.1</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: center;">2.1 Gases. 2.1</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p style="text-align: center;">not regulated</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: | <p style="text-align: center;">Not applicable.</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): | <p style="text-align: center;">Warning: Gases. -</p> |

(Contd. on page 10)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML**

(Contd. of page 9)

| | |
|---|---|
| · EMS Number: | F-D,S-U |
| · Stowage Code | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |
| · Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 11)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE HOBBY&CRAFT SEALER GLOSS 6UC 400 ML

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H201 Explosive; mass explosion hazard.
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.

· **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Expl. 1.1: Explosives – Division 1.1
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

GB