

PlastiKote Chalk Colours 400 ml

Ord.-no.: look at ordering information

Technical Information



PlastiKote Chalk is the water-based chalk finish spray paint that gives a vintage look to furniture, mirrors, picture frames and ornaments. Available in a range of diverse heritage colours, it gives an ultra-matt chalky finish and is perfect for anyone with an interest in interior design. Chalk spray paint can be sanded and washed back from just ten minutes after application to create a rustic distressed look - perfect for a shabby chic finish. Our Chalk spray paint can be used on virtually any surface, making it ideal for use on wooden furniture and upcycling projects. With an environmentally friendly water-based formula, our Chalk finish spray paint is odour-free - perfect for painting indoors or outdoors.

Quality & properties

- Diverse heritage colours
- Ultra matt, chalky finish
- Water-based with a gentle spray mist action
- Eco-friendly with a low solvent content
- Any mistakes can be simply washed away with soap and water within ten minutes.

Physical & chemical data

- Base: Waterbased acrylic resin
- Colourname:
 - ◊ Caffe Espresso
 - ◊ Vintage white
 - ◊ Old Hessian
 - ◊ Dark Hessian
 - ◊ Frost Blue
 - ◊ Pastel Green
 - ◊ Pale Rose
 - ◊ Antique White
 - ◊ Classic Duck Egg
 - ◊ Dove Grey
- Degree of gloss: flat mat, <4 GU
- Efficiency: 400 ML – 1 - 1,4 m²
- Dust dry: 10 min
- Dry to touch: 20 min
- Completely dry: 12 h
- Overcoatable: 10 min
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- pH-Value: 9,3
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com